



Ürün QR Kodu



Product QR Code

Hidrolik Mantar Bariyer (Hidrolik Ünitesi Dışında)

Hydraulic Rising Bollards (External Hydraulic Unit)

Çalışma Voltajı	: 380 Vac 50 Hz
Motor Gücü	: 1,5 - 3 - 4 - 5kW
İşlem Başına, dak/maks	: 20/180
Tahrik Sistemi	: Hidrolik
Kaldırma Pistonu	: 40 x 600 x 25
Hidrolik Hortum	: R2 (Çift Helis) 400 Bar
Dayanım Sürekliliği	: %100
Çalışma Ortam Sıcaklığı	: -20 + 55
Koruma Sınıfı	: IP68
Çalışma Hızı	: 3/8" cm/s
Güvenlik Sistemi	: Loop Sensörü, Emniyet fotoseli, LED ışık
Gövde	: Ø323mm ST37 4 mm Derinlik
Hareketli Bariyer Parçası	: Ø273 St44 10mm Üst üst 2mm CR304 sta. çelik
Yüzey Kaplama	: Tüm yüzey sıcak daldırma galvaniz, 2mm CR304 paslanmaz çelik
Montaj	: Sertleştirilmiş taban çevresi dökme beton
Kontroller	: Mikroişlemci kartı, uzaktan kumanda

Working Voltage	: 380 Vac 50 Hz
Engine Power	: 1,5 - 3 - 4 - 5kW
Per Operation, min/max	: 20/180
Drive System	: Hydraulic
Lifting Piston	: 40 x 600 x 25
Hydraulic Hose	: R2 (Double Helix) 400 Bar
Continuity of Durability	: % 100
Operating Temperature	: -20 + 55
Ingress Protection	: IP68
Operating Speed	: 3/8" cm/s
Safety System	: Loop Sensor , Safety photocell , LED light
Body	: Ø323mm ST37 4 mm Steel
Moving Barrier Part	: Ø273 St44 10mm Steel top 2mm CR304 sta. steel
Surface Coating	: All surfaces are hot-dipped galvanized, with 2mm CR304 stainless steel
Assembly	: Cast concrete surrounding hardened base
Controls	: Micro-processor card, remote control

